

Package: deformula (via r-universe)

September 18, 2026

Type Package

Title Integration of One-Dimensional Functions with Double Exponential Formulas

Version 0.1.3

Description Numerical quadrature of functions of one variable over a finite or infinite interval with double exponential formulas.

URL <https://github.com/okamumu/deformula/>

BugReports <https://github.com/okamumu/deformula/issues>

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

LinkingTo Rcpp

Imports Rcpp

Suggests covr, testthat (>= 3.0.0)

Config/testthat/edition 3

Repository <https://okamumu.r-universe.dev>

Date/Publication 2026-09-10 03:47:21 UTC

RemoteUrl <https://github.com/okamumu/deformula>

RemoteRef HEAD

RemoteSha 8621225c4af1c2040ee56bf8f63f0e1692c263bf

Contents

deformula-package	2
deformula.moneone	2
deformula.zeroinf	3
Index	5

deformula-package	<i>deformula: Integration of One-Dimensional Functions with Double Exponential Formulas</i>
-------------------	---

Description

Numerical quadrature of functions of one variable over a finite or infinite interval with double exponential formulas.

Author(s)

Maintainer: Hiroyuki Okamura <okamu@hiroshima-u.ac.jp> ([ORCID](#))

See Also

Useful links:

- <https://github.com/okamumu/deformula/>
- Report bugs at <https://github.com/okamumu/deformula/issues>

deformula.moneone	<i>Integration of one-dimensional functions over finite interval with the double exponential formula.</i>
-------------------	---

Description

Numerical quadrature of functions of one variable over (lower, upper) with the double exponential formula.

Usage

```
deformula.moneone(  
  f,  
  lower,  
  upper,  
  ...,  
  zero.eps = 1e-12,  
  rel.tol = 1e-08,  
  start.divisions = 8,  
  max.iter = 12  
)
```

Arguments

<code>f</code>	An R function taking a numeric first argument.
<code>lower</code>	The lower limit of integration.
<code>upper</code>	The upper limit of integration.
<code>...</code>	Additional arguments to be passed to 'f'.
<code>zero.eps</code>	A threshold value to be zero.
<code>rel.tol</code>	A relative accuracy requested.
<code>start.divisions</code>	An integer. The initial number of subintervals.
<code>max.iter</code>	An integer for the maximum number of iterations to increase subintervals.

Value

A list with components;

<code>value</code>	A value for integral.
<code>x</code>	A vector of subintervals.
<code>w</code>	A vector of weights.
<code>t</code>	A vector of subintervals for trapezoid integral.
<code>h</code>	A value of subinterval.
<code>message</code>	OK or a string for the error message.

Examples

```
f <- function(x, a) exp(-a*x)
deformula.moneone(f, 0, 1, a=0.1)
```

<code>deformula.zeroinf</code>	<i>Integration of one-dimensional functions over infinite interval with the double exponential formula.</i>
--------------------------------	---

Description

Numerical quadrature of functions of one variable over $[0, \infty)$ with the double exponential formula.

Usage

```
deformula.zeroinf(
  f,
  ...,
  zero.eps = 1e-12,
  rel.tol = 1e-08,
  start.divisions = 8,
  max.iter = 12
)
```

Arguments

<code>f</code>	An R function taking a numeric first argument.
<code>...</code>	Additional arguments to be passed to 'f'.
<code>zero.eps</code>	A threshold value to be zero.
<code>rel.tol</code>	A relative accuracy requested.
<code>start.divisions</code>	An integer. The initial number of subintervals.
<code>max.iter</code>	An integer for the maximum number of iterations to increase subintervals.

Value

A list with components;

<code>value</code>	A value for integral.
<code>x</code>	A vector of subintervals.
<code>w</code>	A vector of weights.
<code>t</code>	A vector of subintervals for trapezoid integral.
<code>h</code>	A value of subinterval.
<code>message</code>	OK or a string for the error message.

Examples

```
f <- function(x, a) exp(-a*x)
deformula.zeroinf(f, a=0.1)
```

Index

`deformula (deformula-package)`, [2](#)
`deformula-package`, [2](#)
`deformula.moneone`, [2](#)
`deformula.zeroinf`, [3](#)